

Product Brochure For D171

## Industrial Geared Head Drilling Machine - GHD-22A

Ø25mm Drilling Capacity

**On Sale**

Ex GST

Inc GST

~~\$2,450.00~~

~~\$2,695.00~~

**\$2,150.00**

**\$2,365.00**



ORDER CODE:	D171
MODEL:	GHD-22A
Drilling Capacity (mm):	Ø25
Thread Tapping Capacity (Metric):	~
Spindle Taper (MT):	3
Spindle Travel (mm):	125
Throat Depth (mm):	255
Quill Diameter (mm):	60
Column Diameter (mm):	100
Spindle To Table (mm):	830
Spindle To Base (mm):	1240
Table (Type):	Rectangle
Table Size (mm):	350 x 500
T-Slot Size (mm):	14
Automatic Quill Feed (mm/rev):	~
Work Light (Includes):	~
Coolant System (Includes):	~
Spindle Speed Steps (No.):	8
Spindle Speed Range (rpm):	105 ~ 2900
Motor Power (kW / hp):	0.9 / 1.2
Voltage / Amperage (V / amp):	415
Full Height (mm):	1800
Nett Weight (kg):	220



### Description

The GHD-22A Industrial Drilling Machine features a 3 Morse Taper spindle geared head rather than a pulley and belt drive system, making adjusting speed faster and simpler. Using this machine is straightforward, thanks to its large cast table with 14mm T-slots, which rotates 360° and uses a rack and pinion to adjust its height. Drilling speeds vary from 105 to 2900rpm and, there is a drill depth stop for accurate and repeatable drilling.

### Features

- Ideal for industrial or workshop use
- Geared head drilling machine with 3 morse taper spindle
- 8 drilling speeds from 105 - 2900 rpm
- High/low with forward & reverse switch
- Helical cut gears for quiet & smooth operation
- Interlocked spindle safety guard
- Rack and pinion wind-up drill head
- Rack & pinion table height adjustment with locking lever
- Thick walled column ensuring greater rigidity
- Drill ejector lever
- Safety emergency stop/reset switch
- Table rotates 360°
- Drilling depth stop setting with scale
- T slotted work table

### Includes

- 16mm keyed drill chuck and arbor
- Chuck key to suit
- Drill drift tool to remove drill chuck or taper shank drills
- Interlocked spindle safety guard

Product Brochure For D171

Specific Features



Left View



Quill Handle



T Slotted Work Table With 360 Degree Rotation



Rack & Pinion Wind Up Drill Head



Drill Chuck



High/Low With Forward & Reverse & Spindle Speeds



Switch Panel

Recommended Accessories

D1272

Metric 135° Precision HSS Drill Set - 25 Piece



D1282

Imperial 135° Precision HSS Drill Set - 29 Piece



D1285

Metric 135° Precision HSS Drill Set - 51 Piece



S090A

Soluble Metal Cutting Fluid - 1 Litre



Product Brochure For D171

S090

Soluble Metal Cutting Fluid - 5 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste - 200g



S074

Cutting Tool Lubricant Paste - 500g



L300

Magnetic Swarf Remover



M9991

Magnetic Floor Sweeper



D1171

Metric Industrial HSS Reduced Shank Drill Set



D1181

Imperial Industrial HSS Reduced Shank Drill Set



D117

Metric HSS Reduced Shank Drill Set



C289

Heavy Duty Drill Chuck - Keyed Type



C290

Heavy Duty Drill Chuck - Keyed Type



Product Brochure For D171

**C292**  
 Industrial Drill Chuck - Keyless Type



**C294**  
 Industrial Drill Chuck - Keyless Type



**D443**  
 3MT x JT6 Drill Chuck Arbor




**D443A**  
 3MT x JT3 Drill Chuck Arbor



**D424**  
 Drill Sleeve - Morse Taper



**C0965**  
 Clamp Kit 58 piece - Workshop Series



**V141**  
 Safeway Precision Drill Press Vice



**V142**  
 Safeway Precision Drill Press Vice



**V143**  
 Safeway Precision Drill Press Vice



**V138**  
 Drill Press Vice



**V139**  
 Drill Press Vice



**T004B**  
 Tapping Chuck - Fixed



Product Brochure For D171

T004

Reversible Tapping Chuck - Adjustable Clutch



T005

Reversible Tapping Chuck - Adjustable Clutch




M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



O000

SpillFix Universal Organic Absorbent



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive



O044

Rust & Corrosion Preventive

