

## Product Brochure For H268

### Electric Chain Hoist - 2S

2 Tonne x 6 Metre Lift  
 Single Speed: 2.3m/min. Lift Speed



**Special Order**

<b>Ex GST</b>	<b>Inc GST</b>
<b>\$5,895.45</b>	<b>\$6,485.00</b>

ORDER CODE:	H268
MODEL:	2S
Capacity (Tonne):	2
Lift Height (Metre):	6
Lift Speed (m/min):	2.3
Motor Power (W):	800
Voltage (V):	415

**HITACHI**  
Inspire the Next



#### Description

Hitachi's reputation for excellence in design, quality, reliability and performance has made this brand a global market leader. With over three decades of proven reliability throughout Australasia and an extensive operating range, Hitachi Electric Chain Hoists are suited to most applications. The Hitachi models vary from 250kg to 5 tonne capacity and are available in three or single phase, two speed or single speed while being tested to the Australian standards

#### Features

- All Hitachi models are manufactured to comply with AS1418.2.
- Operation: fully contactorised with high rated contactors and pendant controls; both fitted with mechanical interlocks and 24 Volt control. Optional IP65 pendant including E-Stop available.
- Safety Limits: full current and shunt limit switches operate in both directions of hook travel.
- Overload Limiter: this electro-mechanical device is exclusive to the Hitachi range and boasts a far more superior overload protection device than the slipping clutch method. Available on all Hitachi models.
- Braking: all models are fitted with an electro-magnetic, self-adjusting disc type brake to the gearbox and the 'F' models have an additional auxiliary centrifugal brake fitted to the motor.
- Completely enclosed design. Entire mechanism including; the motor, dual brake system, gears, rotating parts and electrical system can be operated under severe conditions.
- Chain Bucket: noiseless design with flexible mounting.
- High quality Grade 80 zinc plated load chain supplied as standard.
- IP54 protection rating on all electric hoists and trolleys.
- Motor thermal protection on all Hitachi models.
- Optional radio remote control.
- Ambient temperature requirement of -10 to 40 degrees.
- Class M4 inclusive of 180 starts per hour.
- Reverse phase protection relay on all models excluding; 250kg, 500kg and all single phase models.
- Special low headroom hoist and trolley arrangements available to suit tight headroom applications.
- Electric trolleys are fitted with Guide Rollers as standard to reduce wear and ensure suitability for curved beam applications.

#### Optional Accessories

- Available with customisable chain lengths and an optional wireless remote for added convenience (additional costs apply)

Product Brochure For H268

**Recommended Accessories**

C148  
 Girder Trolley



H311  
 Round Slings



H310  
 Round Slings



H314  
 Round Slings



H315  
 Round Slings



H312  
 Round Slings



H313  
 Round Slings



H322  
 Flat Slings



Product Brochure For H268

---

H324  
Flat Sling

