

Product Brochure For J026

Professional Low Profile Hydraulic Trolley Jack - Steel - ARMGT2

2000kg (2 Tonne) Low Profile
 95 ~ 470mm Lift Height



ORDER CODE:	J026
MODEL:	ARMGT2
Trolley Jack Load Capacity (kg / Tonne):	2000 / 2
Trolley Jack Lift Height (mm):	95 ~ 470
Trolley Jack Fabricated Material (Type):	Steel
Axle Stands Load Capacity (kg / Tonne):	~
Axle Stands Height (mm):	~
Nett Weight (kg):	35



Description

Professional premium quality low profile trolley jack
 Tested to Australian standards

Features

- 2,000kg capacity
- Low profile 95mm minimum height, perfect for jacking vehicles with low ground clearances
- Professional, premium quality low profile trolley jack
- Manufactured and individually tested in Europe
- Manufactured to meet the strictest international safety standards
- Fitted with polyamide wheels and castors to facilitate manoeuvrability
- Foot pedal for quick approach of lifting saddle to load
- 900mm jack length, 1610mm long with handle
- 360mm wide at rear and 257mm wide at front of jack
- Safety overload valve which prevents the jack from being used beyond the rated capacity
- Lowering operation by the "dead man's" principle (the operation is halted if the user accidentally loses control)
- High quality durable seals and internal components for extended service life
- Tested to AS/NZS 2693, ANSI PALD & EN1494 Standards

Product Brochure For J026

Specific Features



ARMGT2 Jack

Recommended Accessories

A332

Hydraulic Vehicle Positioning
Jacks

