

Product Brochure For K0172B

Package Deal - RAZOR 200 AC/DC TIG WELDER High Frequency

PULSE FUNCTION
 5-200 Amps TIG Welding Range

Limited Stock

Ex GST

Inc GST

\$2,133.64

\$2,347.00



| | |
|---|-------------------------------|
| ORDER CODE: | K0172B |
| Type: | TIG WELDER |
| MODEL: | RAZOR™ 200 AC/DC |
| Part Number: | U12002K |
| Voltage / Amperage (V / amp): | 240 / 10 |
| Recommended Plug (amp): | 10 |
| Input Frequency (Hz) (Hz): | 50 |
| Input Current (amp): | ~ |
| Imax (A) (amp): | ~ |
| Ieff Current (amp): | ~ |
| Power Rating (kVA): | 9.0 |
| Rated Output Current (amp / V): | 5-200A |
| Range of Output Current (amp): | 5- 200 - TIG & 20 - 160 - MMA |
| Arc Force (amp): | ~ |
| No Load Voltage (V): | 65 |
| Pre-Flow (S) (sec): | ~ |
| Clean Width (%) (%): | ~ |
| Slope-Down Time (S) (sec): | ~ |
| Post-Flow Time (sec): | ~ |
| Base Current (%): | ~ |
| Pulse Frequency (Hz): | ~ |
| Pulse Duty Cycle (%): | ~ |
| TIG Welding Thickness Range (mm): | ~ |
| MMA Welding Thickness Range (mm): | ~ |
| MMA Electrode Range (mm): | ~ |
| Duty Cycle 40 Deg C - TIG (% @ amp): | 20 @ 200 |
| Duty Cycle 40 Deg C - MMA (% @ amp): | 15 @ 160 |
| Duty Cycle 40 Deg C - Plasma (% @ amp): | ~ |
| Plasma Severance Cut Capacity Carbon Steel (mm): | ~ |
| Plasma Production Cut Capacity Carbon Steel (mm): | ~ |
| Plasma Production Cut Capacity Aluminium (mm): | ~ |
| Dinse Connector: | ~ |
| Protection Class: | IP23S |
| Insulation Class: | H |
| Standard: | ~ |
| Remote Control (Yes / -): | ~ |
| Recommended Generator (kVA): | 9 |
| Efficiency (%): | ~ |
| Power Factor: | ~ |
| Dimensions (mm): | 500 x 170 x 340 |
| Nett Weight (kg): | 11.7 |

Description

HD Backlit Interface
 This next generation interface panel is bright and easy to read in any environment.

Power Factor Correction (PFC)
 PFC gives you maximum electrical efficiency. It automatically compensates for any voltage fluctuation, and PFC is also designed to be generator friendly.

Product Brochure For K0172B

10A Plug

A 10 AMP power plug can be used on any domestic outlet. It's perfect for the DIY home handyman or the professional welder looking for a machine that can be used almost anywhere.

AC/DC

Weld every kind of metal. With the ability to run on an Alternating Current, you're able to weld aluminium as effortlessly as mild and stainless steels.

High Frequency TIG

Maximise your results from start to finish. A high-frequency torch can start an arc without contacting the workpiece, reducing the risk of contaminating the tungsten or the weld. It also means you get access to the entire TIG weld cycle, including pre- and post-gas and up and down slope parameters.

Multiple AC Waveforms

Completely customise your aluminium welds. Switch between Sine, Square, and Triangle waves to change the arc characteristics, bead profile, and penetration to suit your weld.

Mixed AC/DC

Experience the best of both worlds. Mixed AC/DC combines the efficiency of AC and the penetration of DC- TIG in one weld. With it, you get faster welding speeds, better penetration, a faster weld puddle on cold workpieces, and you can weld thicker materials.

Pulse TIG

Minimise the heat input without compromising on any of the penetration. Alternating between a peak and base current reduces the amount of heat input and focuses the arc, perfect for sheet metals and out-of-position welding.

Foot Control Ready

The perfect accessory, easily adjust your amperage to suit every weld as you go without disrupting your torch movement.

Smart Fan

Smart Fan diminishes noise, saves power, helps reduce energy costs, and minimises the number of contaminants being pulled through the machine.

Advanced MMA Features

The RAZOR TIG 200 AC/DC features adjustable Arc Force and Hot Start functionality. These features are designed for improving weld quality and ease of use.

Optional Remote Control

Upgrade your machine with a handy remote control. Both a wired and wireless controller are available.

Features

- Effortlessly weld any metal with the high-frequency AC/DC TIG
- The ultimate combination of AC and DC available with Mixed Arc settings
- Switch your AC welds to suit your needs with the choice of three waveforms
- 5-year warranty

Includes

- BONUS Foot Control (W1722A)
- RAZOR TIG 200 AC/DC Welder
- 8m T2 TIG Torch
- 4m Twist Lock Electrode Holder
- 4m 300 Amp Earth Clamp & Lead
- Argon Flowmeter Regulator
- 1.8m Gas Hose with fittings
- Operating Manual

Product Brochure For K0172B

Specific Features



Complete Machine Kit



Front

Recommended Accessories

W241
 Universal Welder Trolley



W2415
 TRI-CART Multi-Machine
 Welding Trolley



W1722A
 Suits RAZOR AC/DC 200 Tig
 Welder



W504A
 T2 Tig Torch Consumable Pack



W10361
 Magnetic TIG Torch Rest



W101
 TIG Welding Gloves - 310mm



O0184
 Ar/O₂ - Argon 98% & Oxygen
 2% Disposable Cylinder



O0185
 CO₂/Ar - 86% Argon & 14%
 Carbon Dioxide Disposable
 Cylinder



Product Brochure For K0172B

O300
 Gas Refillable Cylinder



O304
 Gas Refillable Cylinder



O3045
 Gas Refillable Cylinder



O302
 Gas Refillable Cylinder



O306
 Gas Refillable Cylinder



O3065
 Gas Refillable Cylinder



W501A
 M350 MIG Torch Consumables
 Starter Kit



O0171
 Argon Gas Regulator



W161
 Argon Gas Regulator-Bobbin
 Flowmeter



W160A
 Argon Gas Regulator-Twin
 Gauge



W5991
 Ø10mm Ceramic Nozzle



W5993
 1.6mm Collet Body



Product Brochure For K0172B

W5994
 2.4mm Collet Body



W5996
 Head Gasket



W5997
 Heat Isolator



W5998
 Long Black Cap



W5999
 Short Back Cap



W590
 1.6mm Tig Tungsten Electrode - Zirconiated White



W596
 2.4mm Tig Tungsten Electrode - Zirconiated White



W597
 1.6mm Tig Tungsten Electrode - Ceriated Grey



W598
 2.4mm Tig Tungsten Electrode - Ceriated Grey



W002
 Auto Darken Welding Helmet - 9-13 Shade



W1000A
 Promax HV5 Welding Jacket



W1001A
 Promax Blue FR Welding Jacket



Product Brochure For K0172B


W1002A
 Professional Promax BL7
 Welding Jacket



W100
 ROGUE™ Heavy Duty Welding
 Gloves - 400mm



L3456
 How to Weld Book



W225
 Welding Curtain



W125
 Ø1.6mm TIG Filler Rod - Mild
 Steel



W126
 Ø2.4mm TIG Filler Rod - Mild
 Steel



W127
 Ø1.6mm TIG Filler Rod -
 Stainless Steel



W128
 Ø2.4mm TIG Filler Rod -
 Stainless Steel

