

Product Brochure For K8250

Centre Lathe - Includes Tooling Package - AL-1324, 240V

Built to School Specifications
 NSW DOE Item 32A

Please Call



ORDER CODE:	K8250
NSW DOE Item No.:	32A
QLD DOE Item No.:	~
MODEL:	Schools/TAFE AL-1324 &
Digital Readout:	Optional
Tool To Suit (mm):	16
Distance Between Centres (mm):	600
Swing Over Bed (mm):	330
Swing Over Gap (mm):	~
Swing Over Cross-slide (mm):	200
Centre Height (mm):	165
Spindle Bore (mm):	Ø40
Camlock Spindle Size:	D1-4
Bed Width (mm):	190
Head Stock Spindle Taper (MT):	5
Tail Stock Taper (MT):	3
Cross Slide Travel (mm):	175
Compound Slide Travel (mm):	100
Lead Screw:	Metric
Cross Feed (mm/rev):	0.034 ~ 0.468
Longitudinal Feed (mm/rev):	0.068 ~ 0.936
Metric Thread Range (No. / mm):	30 (0.4 - 7.0)
Imperial Thread Range (No. / TPI):	32 (4 - 56)
3 Jaw Chuck Diameter (mm):	Ø160
4 Jaw Chuck Diameter (mm):	Ø200
Spindle Steps/speeds (No. / RPM):	9 / 82-2000
Motor Power (kW / hp):	1.5 / 2
Voltage / Amperage (V / amp):	240 / 15
Nett Weight (kg):	660



Description

The AL-1324 is proudly manufactured in Taiwan and is equipped with all the necessary safety features to meet the standards set by the education department. This machine includes a leadscrew cover, a chuck guard with a micro switch, a micro switch on the side access door, and an emergency foot brake. These advanced safety features make the AL-1324 an excellent choice for protecting students as they learn and develop their skills.

Features

- Toolroom quality precision lathe
- Manufactured in Taiwan and sold for over 25 years
- Gear drive headstock for quick change of spindle speeds
- Stand increasing rigidity and reducing vibration
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Change gears for metric and imperial thread cutting
- Oil sight glass for head stock and gearbox
- Adjustable taper roller bearings support the spindle
- 2HP/240V motor, 9-speed (82 - 2000rpm)
- Enclosed quick action gearbox for thread cutting and auto feeding
- Powered longitudinal and cross feeds
- D1-4 camlock spindle for quick chuck changes and safe reverse-direction turning. ISO standard
- Dual calibrated dials
- Coolant system with flexible hose
- Slide out swarf tray

Safety Features

- Foot operated spindle brake with safety cut out switch
- Interlocked safety chuck guard
- Interlocked change gear cover with integrated tool-locking mechanism
- Leadscrew cover ensures swarf not reaching clasp nut

Product Brochure For K8250

- Emergency stop switch fitted to headstock
- Overload protection on drive motor and coolant system
- Overload clutch mechanism on auto power feed
- Keyed isolation switch - PWD approved
- Test and tag certificate on 240V lead

Includes

- Ø160mm 3-jaw chuck with reverse jaws - D1-4 mount
- Ø200mm 4-jaw chuck - D1-4 mount
- Ø200mm Drive Plate - D1-4 mount
- Fixed Steady
- Travelling steady
- Dead centre
- Spindle reducing bush
- Thread chasing dial
- Rear splash guard
- 16mm Turning Tool Kit (L451)
- Parting Tool Holder (L074)
- HSS Parting Blade (L0007)
- 13mm Keyless Drill Chuck (C292)
- 3MT x JT6 Drill Chuck Arbor (D443)
- 3MT Live Centre (C052)
- Knurling Tool Holder - Clamp type (L080)
- Lathe Carrier 38mm - Bent tail (L081)
- 6 x Machine mounts - 500kg capacity (M002)
- Spanners, toolbox & operators manual

Specific Features



Left View



Chuck Guard with Safety Micro



Safety Chuck Guard Up



Headstock



Spindle Speed Levers

A	B	C
300	2000	1400
82	550	400
165	1100	770

Spindle Speed Chart




Enclosed Quick Change Gearbox


PITCH (MM)			
127	127	T	U
127	127	S	R
127	127	X	Y
127	127	Z	Z
AD	32	36	40
AD	48	50	56
AD	60	70	70
BD	16	18	20
BD	24	25	28
BD	30	35	35
AC	08	09	10
AC	14	15	15
BC	04	05	06
BC	07	07	07
T.P.I.			
127	127	U	T
127	127	T	T
127	127	X	X
127	127	X	X
127	127	X	X
AD	4	4	4
AD	5	5	5
AD	6	6	6
BD	8	9	10
BD	11	12	14
AC	16	18	20
AC	22	24	28
BC	32	36	40
BC	44	48	56
FEED			
127	127	X	Y
127	127	Y	Z
PAD	0.544	0.752	0.936
PBD	0.272	0.376	0.468
PAC	0.136	0.188	0.234
PBC	0.068	0.094	0.117

Thread & Feed Chart


Product Brochure For K8250



Saddle Hand Wheel




Compound Slide Hand Wheel



Compound Slide



Tailstock



Tailstock Hand Wheel



Tailstock Quill Graduations



Tailstock Horizontal Adjustment



Hardened and Ground Bedways



Bed Drip tray



Toolbox



16mm Turning Tool Kit L451



Parting Tool Holder L074



HSS Parting Blade L011B



13mm Keyless Drill Chuck C292



3MT x JT6 Drill Chuck Arbor D443



3MT Live Centre C052

Product Brochure For K8250



Knurling Tool Holder Clamp Type-L080



6 x 500kg capacity Machine Mounts M002



Lathe Carrier 38mm Bent Tail-L081



Drive Plate

Recommended Accessories

A358

Sky Hook Lifting Device

A358A

Chuck Hook

L457

Lathe Threading Tool Kit - Insert Type

L465

Professional Lathe Parting Tool Kit - Insert Type



L341

Fitting and Machining Technical Book

L295

Quick Change Toolpost

L295A

Quick Change Toolpost Holder - Std

M800

Rubber Mat - Anti-Fatigue Std

