

Product Brochure For K8411

## 30 Tonne Workshop Hydraulic Press with Guarding - HPM-30

Built to School Specifications  
 NSW DOE Item 27

### Please Call



ORDER CODE:	K8411
NSW DOE Item No.:	27
QLD DOE Item No.:	~
MODEL:	School / TAFE HPM-30
Capacity (Tonne):	30
Sliding Ram (Yes / No):	Yes
Width Between Front Posts (mm):	535
Width Between Side Posts (mm):	138
Ram To Table (Max.) (mm):	1035
Cylinder Stroke (mm):	155
Ram Diameter (mm):	Ø70
Piston Diameter (mm):	Ø80
Floor Space (W x D x H) (mm):	950 x 700 x 1800
Nett Weight (kg):	200



### Description

The Metalmaster HPM-30 30 tonne trade press has a variety of uses, ideal for removing and installing bushes, ball joints, bearings, gears, pulleys etc. The HPM-30 is hand operated for easy use and also has the added feature of a sliding head which can be moved to the side allowing for those offset pressing jobs.

### Features

- Ideal for removing and installing - Bushing, Ball-joints, Bearings, Gears, Pulleys, etc
- Pneumatic or hand operation
- Heavy duty steel construction with robotic fully welded frame
- Hydraulics assembled in a temperature controlled clean room for maximum quality
- Hydraulics individually factory tested prior to shipping.
- Adjustable sliding head up to 200mm travel between the vertical post
- Metric / imperial pressure gauge included

### Safety Features

- Front and rear safety guarding that is manually adjustable in height to allow access for your workpiece.

### Includes


- Complete with vee blocks
- Front and rear safety guarding

Product Brochure For K8411

Specific Features



Side View Safety Guards



Safety Guard Quick Release with Table Height Adjustment With Safety Clips



Horizontal Sliding Ram



Ram



Vee Blocks Shown



Ram Top View With Bearing Slide



Pressure Gauge



Includes Removable Ram Top Cap

Recommended Accessories

O002

Superdraulic ISO 46 Hi Temp Hydraulic Oil



O004

Superdraulic ISO 46 Hi Temp Hydraulic Oil

