

Product Brochure For K8702

GHD-38B Geared Head Drill - QLD Schools / TAFE

40mm

QLD Contract Item No. 2.4

Please Call



| | |
|--|------------------------|
| ORDER CODE: | K8702 |
| NSW DOE Item No.: | ~ |
| QLD DOE Item No.: | 2.4 |
| MODEL: | Schools / TAFE GHD-38B |
| Bench / Pedestal Type: | Pedestal |
| Duty Type: | Industrial-Duty |
| Drill Capacity (mm): | Ø40 |
| Spindle Taper (MT): | 4 |
| Threading Capacity: | M24 |
| Auto Feed (Yes / No): | Yes |
| Spindle Travel (mm): | 180 |
| Throat Depth (mm): | 350 |
| Quill Diameter (mm): | 75 |
| Collar Diameter (mm): | ~ |
| Column Diameter (mm): | 150 |
| Spindle To Table (mm): | 770 |
| Spindle To Base (mm): | 1320 |
| Table Shape: | Square |
| Micro Switch On Pulley Guard (Yes / No): | No |
| Table Size: | 560 x 560 |
| Spindle Drive Type: | Geared Head |
| Spindle Steps (No.): | 18 |
| Spindle Speeds (RPM): | 50 ~ 1450 |
| Motor Power (kW / hp): | 1.5 / 2 |
| Voltage / Amperage (V / amp): | 415 |
| Overall Height (mm): | 2220 |
| Nett Weight (kg): | 615 |



Features

- Geared head drilling machine with 4MT spindle
- 40mm drill capacity with 180mm of spindle travel
- 18 drilling speeds from 50-1450rpm
- Automatic feed range (0.1, 0.2mm/rev)
- Adjustable accurate depth setting with auto feed cut out
- Drill ejector incorporated in machine
- Automatic thread tapping with auto reversal of direction upon reaching the preset depth

Safety Features

- Emergency stop switch
- Interlocked spindle safety guard
- OPTIONAL SAFETY ELECTRICS
- (D201) - Knee operation emergency stop

Includes


- Coolant system
- Keyless drill chuck
- Arbor & work light
- (V143) 160mm Precision drill vice
- (C294) 16mm keyless drill chuck
- (D454A) 4MT x JT3 Drill chuck arbor
- (D420) 2-1MT sleeve
- (D422) 3-2MT sleeve
- (D424) 4-3MT sleeve
- (C087) Tee nuts 16mm table slot
- (N086) M12 Flanged Nuts
- (N0893) M12 x 75mm Long Double End Threaded Clamp Stud

Product Brochure For K8702

Specific Features



High Low with Forward and Reverse Switch



18 Drilling Speeds from 50 1450rpm



Gear Selection Levers



Adjustable accurate depth setting with auto feed cut out for increased productivity



Head Controls



Automatic Feed Range and Auto Drift Drill Ejector




Emergency Stop Switch and Overload Protection



Work Light



Chuck Guard with Micro Switch




T Slotted Work Table



T Slotted Base



Rack and pinion wind up Table



Coolant Pump System



C087 Tee Nuts 16mm Table Slot



C294 16mm Keyless Drill Chuck



D420 2 1MT Sleeve

Product Brochure For K8702



D422 3 2MT Sleeve



D424 4 3MT Sleeve



D454A 4MT x JT3 Drill Chuck Arbor



V143 160mm Precision Drill Vice



N086 M 12 Flanged Nuts



N0893 Double End Threaded Clamp Stud

Recommended Accessories

D201
 Knee Stop Switch with Bracket
 & 3M Lead



D339
 4MT Morse Taper Shank Drill Bit



D454
 4MT x JT6 Drill Chuck Arbor



D425
 Drill Sleeve - Morse Taper



Product Brochure For K8702

T005B
 Tapping Chuck - Fixed



C289
 Heavy Duty Drill Chuck - Keyed Type



C292
 Industrial Drill Chuck - Keyless Type



C290
 Heavy Duty Drill Chuck - Keyed Type



C294
 Industrial Drill Chuck - Keyless Type



C096A
 Clamp Kit 58 piece - Industrial Series



V141
 Safeway Precision Drill Press Vice



V142
 Safeway Precision Drill Press Vice



V143
 Safeway Precision Drill Press Vice



V138
 Drill Press Vice



V139
 Drill Press Vice




M800
 Rubber Mat - Anti-Fatigue



Product Brochure For K8702

M805
Rubber Mat - Anti-Fatigue



S090A
Soluble Metal Cutting Fluid - 1 Litre



S090
Soluble Metal Cutting Fluid - 5 Litre



S076
Cutting Tool Lubricant Fluid - 500ml



S077
Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075
Cutting Tool Lubricant Paste - 200g



S074
Cutting Tool Lubricant Paste - 500g



O000
SpillFix Universal Organic Absorbent



O043
Rust & Corrosion Preventive



O042
General Purpose Lubricant & Corrosion Inhibitor



O040
Rust & Corrosion Preventive



O044
Rust & Corrosion Preventive

