

Product Brochure For L569D

Centre Lathe - AL-410

Ø400 x 1000mm Turning Capacity - Ø52mm Spindle Bore
 Includes Digital Readout System & Quick Change Toolpost



On Sale

Ex GST	Inc GST
\$9,450.00	\$10,395.00
\$9,090.00	\$9,999.00

ORDER CODE:	L569D
MODEL:	AL-410
Swing Over Bed (mm):	400
Distance Between Centres (mm):	1000
Spindle Bore (mm):	52
Swing In Gap (mm):	520
Swing Over Cross-slide (mm):	250
Digital Readout System Fitted:	Yes
Quick Change Toolpost Fitted:	Yes
Leadscrew Covers Fitted:	Yes
Taper Turning Attachment:	~
Coolant System:	Yes
Tool Height To Suit (mm):	16
Centre Height (mm):	200
Spindle Nose Size or Type:	D1-5 Camlock
Bed Width (mm):	218
Headstock Spindle Taper (MT):	6
Tailstock Taper (MT):	4
Cross Slide Travel (mm):	250
Compound Slide Travel (mm):	80
Leadscrew Type:	Metric
Metric Cross Feed (X-Axis) (mm/rev):	0.011 - 0.276
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	0.052 - 1.291
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	32 (0.4 - 7)
Imperial Thread Steps & TPI (No. / TPI):	36 (4 - 60)
3 Jaw Chuck Diameter (mm):	200
4 Jaw Chuck Diameter (mm):	200
Spindle Steps / Speeds (No. / rpm):	18 (65 - 2000)
Motor Power (kW / hp):	2.4 / 3.2
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	850

Features

- 2 Axis digital readout system
- Quick change toolpost with 5 holders
- Concertina leadscrew cover
- Gear drive headstock for quick change of spindle speeds
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Low voltage work light
- Foot operated spindle brake with safety cut out switch
- Slide out front swarf tray for easy cleaning
- Change gears for metric and imperial thread cutting
- Oil sight glass for head stock and gearbox
- Adjustable taper roller bearings support the spindle
- Inching button is incorporated on the control panel for convenient spindle speed selection
- Enclosed quick action gearbox for thread cutting and auto feeding
- Powered longitudinal and cross feeds
- D1-5 camlock spindle for quick chuck changes and safe reverse-direction turning. ISO standard
- Removable gap bed-way for larger diameter jobs

Product Brochure For L569D

- Dual calibrated dials (except for saddle hand-wheel)
- Chuck & change gear guards are fitted with micro switches
- Coolant system with flexible hose
- Slide out swarf tray

Includes

- 2 Axis digital readout system
- Concertina leadscrew covers
- Slide out front swarf tray
- Quick change tool-post with 5 holders
- 200mm 3-jaw chuck with reverse jaws
- 200mm 4-jaw chuck
- Face plate
- Fixed steady
- Travelling steady
- Change gears
- Dead centres
- Thread-chasing dial
- Work light
- Stand
- Rear splash guard & swarf tray
- Tool box
- Instruction booklet

Specific Features



2 Axis Digital Readout



Three Tool Draws



Induction Hardened Bedways



Safety Chuck Guard



Quick Change Toolpost



Leadscrew Covers



Spindle Speed Levers

		Spindle Speed		
		○ / min		
		1	2	3
H	A	400	2000	1200
	B	110	550	320
	C	308	1520	930
L	A	198	980	600
	B	55	270	165
	C	150	760	460

Spindle Speed Chart

Product Brochure For L569D



Feed and Thread Gearbox



Saddle Right View



Saddle Stop




Coolant Hose and Worklight




Coolant Pump




Compound Slide



Saddle Left View



Saddle Front View




Feed and Thread Engagement Levers




Thread Chasing Dial

INDICATOR TABLE					
T	mm	SCALE	T	mm	SCALE
0	0.5	15	0.45	1	15
	0.6	15	0.9	1	15
	0.75	15	1.25	1	15
	1	15	1.8	1	15
16	1.5	15	2.25	1	15
	3	15	2.50	1	15
	0.4 1-8	14	4.50	1	14
	0.8 1-3-5-7	14	5	1	14
14	1.2 1-8	14	0.7 1-5	1	14
	1.6 1-5	14	1.4 1-5	1	14
	2 1-8	14	1.75 1-5	1	14
	2.4 1-3-5-7	14	2.8 1	1	14
	3.2 1	14	3.5 1-5	1	14
	4 1-3-5-7	14	7 1-5	1	14
	4.8 1-5	14			
	8 1-8	14			

Indicator Table



Fixed & Travelling Steadies



Saddle Hand Wheel



Saddle Hand Wheel Graduation



Spindle Engagement Lever



Crossslide Hand Wheel

Product Brochure For L569D



Compound Slide Hand Wheel



Swivel Compound Slide




Tailstock



Tailstock Quill



Tailstock Hand Wheel



Slide Out Drip Tray



Foot Brake



Feed Charts

METRIC THREAD PITCH LIST										
	B4	C4	C3	C2	A4	D2	E4	A2	E2	
MI	0.4	0.45	0.5		0.6			0.7	0.75	
	0.8	0.9	1		1.2	1.25	1.4	1.5	1.75	
MII	1.6	1.8	2	2.25	2.4	2.5	2.8	3	3.5	
	3.2	3.6	4	4.5	4.8	5	5.6	6	7	

Metric Thread Pitch Chart

THREAD PER INCH									
	A2	A3	C3	A4	C3	C3	A5	B4	
Z	24	24	38	24	22	24	26	24	24
MII	4	4 1/2	9 1/2	5	5 1/2	6	6 1/2	7	7 1/2
MI	8	9	19	10	11	12	13	14	15
Z	48	48	38	48	44	48	52	48	48
MII	16	18	19	20	22	24	26	28	30
MI	32	36	38	40	44	48	52	56	60

Imperial Thread Chart

MODULE THREAD										
	B4	C4	C3	C2	A4	D2	E4	A2	E2	
MI	0.4	0.45	0.5		0.6			0.7	0.75	
MII	0.8	0.9	1		1.2	1.25	1.4	1.5	1.75	
MII	1.6	1.8	2	2.25	2.4	2.5	2.8	3		

Module Thread Chart

D.P. THREAD												
	A2	A3	A4	A1	B3	A5	B4	C1	B1	B5		
MII	16	18	20	24	27	28	30	32	36	42		
MI	32	36	40	48	54	56	60	64	72	84		
T1	66	66	66	66	E3 41	66	66	E2 47	E5 48			
T2	21	21	21	21	21	22	21	24	28			
MII	8	9	10	12	13	14	15	11	22			
MI										22	44	

DP Thread Chart

Product Brochure For L569D

Recommended Accessories

L277
 Vertical Mill Slide



L017
 Right Hand Turning Tool Holder



L018
 Left Hand Turning Tool Holder



L044
 Right Hand Turning Tool Holder



L045
 Left Hand Turning Tool Holder



L0077
 Lathe Turning Tool Kit - 7 piece
 Insert Type



L451
 Lathe Turning Tool Kit - 3 piece
 Insert Type



L465
 Professional Lathe Parting Tool
 Kit - Insert Type



Product Brochure For L569D

L457
 Lathe Threading Tool Kit - Insert Type



L076
 Knurling Tool Holder Kit



C054
 4MT Live Centre



C046
 4MT Pipe Centre - 70° Cone



C290
 Heavy Duty Drill Chuck - Keyed Type



C294
 Industrial Drill Chuck - Keyless Type



D454A
 4MT x JT3 Drill Chuck Arbor



D1272
 Metric 135° Precision HSS Drill Set - 25 Piece



D1282
 Imperial 135° Precision HSS Drill Set - 29 Piece



D126
 Metric 135° Precision HSS Drill Set - 170 Pieces



S090A
 Soluble Metal Cutting Fluid - 1 Litre



S090
 Soluble Metal Cutting Fluid - 5 Litre



Product Brochure For L569D

S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste - 200g



S074

Cutting Tool Lubricant Paste - 500g



S091

Soluble Metal Cutting Fluid - 20 Litre



G659

Lathe Leadscrew Cover Kit - Concertina




G660

Lathe Leadscrew Cover Kit




L341

Fitting and Machining Technical Book



L3455

Professional Sheet Metal Fabrication Book



L300

Magnetic Swarf Remover



M9991

Magnetic Floor Sweeper




M800

Rubber Mat - Anti-Fatigue



Product Brochure For L569D

M805
 Rubber Mat - Anti-Fatigue



O000
 SpillFix Universal Organic Absorbent



O043
 Rust & Corrosion Preventive



O042
 General Purpose Lubricant & Corrosion Inhibitor



O040
 Rust & Corrosion Preventive



O044
 Rust & Corrosion Preventive

