

Product Brochure For M122

Mill Drill - Geared & Tilting Head - HM-36

Table Travel: (X) - 475mm (Y) - 195mm (Z) - 450mm



ORDER CODE:	M122
MODEL:	HM-36
Digital Readout:	Optional
Type:	Vertical
Table Size (mm):	730 x 210
Column Type:	Ø115mm
Spindle Taper - Vertical:	3MT
Spindle Taper - Horizontal:	~
Longitudinal Travel (X-Axis) (mm):	475
Cross Travel (Y-Axis) (mm):	195
Vertical Travel (Z-Axis) (mm):	450
Type of Slides:	Dovetail
Ram Travel (mm):	~
Spindle to Table (mm):	510
Spindle to Base:	~
Spindle Travel / Diameter (mm):	120 / 75
Throat Depth (max.) (mm):	272
Tilting Head (Left ~ Right):	±90°
Tilting Head (Forward ~ Back):	Fixed
Drilling Capacity (mm):	31.5
End Milling Capacity (mm):	28
Face Milling Capacity (mm):	80
Power Feed - Quill (mm/rev):	~
Power Feed - Longitudinal (X-Axis) (mm/min):	Optional
Power Feed - Cross (Y-Axis) (mm/min):	~
Power Feed - Vertical (Z-Axis) (mm/min):	~
Table T-Slot Size (inch / mm):	14
Work Table Load Capacity (kg):	55
Spindle Speeds Vertical (No./ rpm):	6 (95 - 1600)
Spindle Speeds Horizontal (No./ rpm):	~
Spindle Speeds - Universal Head:	~
Motor Power - Vertical Spindle (kW / hp):	1.1 / 1.5
Motor Power - Horizontal Spindle (kW / hp):	~
Motor Power - Universal Head:	~
Voltage / Amperage (V / amp):	240 / 10
Nett Weight (kg):	293

Description

The HM-36 milling machines is similar in overall size to the popular RF31 but with the additional benefit of a 6-speed 95-1600rpm, gear driven head which can be tilted up to 90° either side of the vertical. This feature allows the head to be positioned in a variety of positions, allowing a whole range of milling, slotting, grooving, drilling and boring operations to be carried out.

The usual handle-driven down feed is available for precision drilling and there is a fine manual down-feed control for precise vertical milling.

The motor is controlled by a standard forward and reverse on/off switch.

There is a heavy duty steel stand available as an extra, strongly recommended bearing in mind the weight of the machine.

Also available is a optional power feed attachment which fits to the left hand end of the table and provides a smooth, variable speed longitudinal drive.

Features

- Gear driven head 6 speeds
- Tilting head to ±90° from vertical
- Milling head rotates 360° on column
- Extra large 730 x 210mm ground work table with T-slots

Product Brochure For M122

- Adjustable leadscrew nuts eliminating backlash on both axis
- Fine feed hand wheel operating quill feed
- Forward and reverse on/off switch
- 3MT spindle with 75mm diameter quill
- Adjustable table and drill length stops
- Rack and pinion wind-up head
- Rear slide-way cover and slide clamps on all axis
- Spindle lock for quill
- Table lock on both axis
- Metric dial graduations @ 0.05mm for X & Y axis

Includes

- Drill chuck
- 3MT arbor
- 3MT-2MT drill sleeve
- Face cutter & arbor
- Safety cutter guard

Specific Features



Forward-Reverse & On Off Switch



Fine feed handwheel operating quill feed



Quill Depth Scale



Spindle Speed Selectors

SPINDLE SPEEDS (r/min)			
	I-L	I-M	I-H
50Hz	95	170	280
60Hz	120	210	340
	II-L	II-M	II-H
50Hz	540	960	1600
60Hz	670	1180	1970


Speed Chart



Spindle lock for quill



Face Mill Cutter



Rack and pinion wind up head



Extra large 730mm x 210mm ground work table with T slots



Head Controls



Geared Head



Tilting head to 90 Degrees from vertical

Product Brochure For M122



Tilting Head



Right View



Table Cross Feed Handle



Table Longitudinal Handle



Drawbar



Includes These Accessories



Show mounted to Optional Stand

Recommended Accessories

M230
 Power Feed Unit

M240
 Transformer


L300
 Magnetic Swarf Remover

M9991
 Magnetic Floor Sweeper




Product Brochure For M122


L342
 Electrical Black Book




L341
 Fitting and Machining Technical Book



L3455
 Professional Sheet Metal Fabrication Book



C0965
 Clamp Kit 58 piece - Workshop Series



C926
 Collet & Chuck Set - 20 Piece



C922B
 Collet & Chuck Set - 8 Piece



M3301
 Metric HSS Slot Drill & End Mill Set - 10 Piece



M3321
 Imperial HSS Slot Drill & End Mill Set - 10 Piece



M3280
 13mm HSS End Mill Long Series



M182
 Precision Boring Head Kit



M192
 Boring Head Shank



M180
 Boring Bar Set - 9 piece



Product Brochure For M122

M250
 Parallel Set - 8 Piece



M530
 Universal Milling Kit - 4 Piece



M562
 Face Mill Arbor



M515
 Face Mill 45° - Super High-Rake



L065
 KYOCERA Carbide Inserts - Milling




M528
 Face Mill 90° - Positive Rake




M529
 Face Mill 90° - Positive Rake



L066
 KYOCERA Carbide Inserts - Milling



V004
 Cast Iron Vee Block



V105
 Vertex K-Type Milling Vice



R006
 Vertex Rotary Table



P235
 Coolant Pump & Tank




Product Brochure For M122

M800
 Rubber Mat - Anti-Fatigue



M805
 Rubber Mat - Anti-Fatigue



S090A
 Soluble Metal Cutting Fluid - 1
 Litre



S090
 Soluble Metal Cutting Fluid - 5
 Litre



S076
 Cutting Tool Lubricant Fluid -
 500ml



S077
 Drilling, Tapping & Cutting Tool
 Lubricant Spray - 400g



S075
 Cutting Tool Lubricant Paste -
 200g



S074
 Cutting Tool Lubricant Paste -
 500g



O000
 SpillFix Universal Organic
 Absorbent



O043
 Rust & Corrosion Preventive



O042
 General Purpose Lubricant &
 Corrosion Inhibitor



O040
 Rust & Corrosion Preventive



Product Brochure For M122

O044

Rust & Corrosion Preventive

