

Product Brochure For O003B

ISO 32 Slideway Lube Oil - XDP-SW32

5 Litre

Suits CNC Laser Machines & Machine Tools

Ex GST
\$70.00

Inc GST
\$77.00



ORDER CODE:	O003B
Grade:	ISO 32
Size (Litre):	5
Application:	SLIDE WAY OIL
Suits:	CNC Laser Machines & Machine Tools



Description

XDP-SW32 is an oil based lubricant formulated with highly refined mineral oil and special additives for its use in guides sliders tool-machines. It contains friction modifiers, extreme-pressure additives and demulsifiers which offer unctuousness and facilitate the separation of the coolants. It can be also used in tool-machines gearboxes and mechanical transmission subjected to very high loads.

ISO grade: 32
 Density (15°C): 0,85 g/ml
 Viscosity (40°C): 32 cSt
 Viscosity (100°C): 5.3 cSt
 Viscosity Index: 96
 Flash point: >200°C
 Freezing point: -20°C
 Test 4 balls 40 Kg/1hour: 0.35 mm diameter

Store the product in an area with controlled temperature between 5° C and 40° C.
 Life in unopened packaging: 1 year

Features

- Suitable for CNC Laser Machines and Machine Tool slide ways
- Very high adhesion on metallic surfaces avoiding noises and vibrations.
- Anti-wear and high extreme-pressure properties to enable its use in gearboxes and mechanical transmission for tool-machines.
- Excellent protection against corrosion and oxidation
- DIN 51517 part 3 CLP standardization meet