

Product Brochure For P196F

CNC Punching Machine - PM-80LT-CNC

80 Tonne

Includes CNC Programmable Positioning Table 1000 x 500mm

Please Call



ORDER CODE:	P196F
MODEL:	PM-80LT-CNC
Punching Pressure (Tonne):	80
Punching Table Feed (Type):	CNC Positioning
Punching Table Dimensions (mm):	1000 x 500 (X & Y-Axis)
Punching Ø x Thickness Capacity - Mild Steel (mm):	Ø25 x 23, Ø50 x 12
Channel Flange Punching (h) (mm):	180
Throat Depth (mm):	510
Maximum Stroke Length (mm):	100
Cycle/min (20mm Stroke) (cpm):	28
Table Working Height (mm):	1050
Motor Power (kW / hp):	5.6 / 7.5
Voltage (V):	415
Nett Weight (kg):	2300



Description

The Sunrise Punching Machines are manufactured in Taiwan, also known as Ironworkers are well recognised in our Australian market for the machines being reliable & durable due to their structurally well manufactured unique design & engineering excellence. Sunrise is ISO-9001 certified by BVQI, and our products meet the CE safety requirements and regulations. Sunrise relentlessly seeks continuous improvement and product development to keep a step ahead of their competitors.

The fully-automatic CNC tables are highly efficient and accurate positioning devices to improve your productivity. The controller is easy to learn and operate, so you can start operating almost immediately. The hydraulic clamps with pressure sensor for strong grip of material are standard equipments on the CNC tables. Moreover, hydraulic stripper with exchangeable plates is also standard equipment on the CNC tables to suit various punching operations. Ball transfer units on the support table provide smooth movement of material, and cover with interlock switch ensures operation safety.

Features

- Specially designed hydraulic circuit system provides high performance, efficiency and accuracy
- CNC programmable positioning table 1000 x 500mm (X & Y-Axis)
- CNC table drive by two 500-watt MITSUBISHI servo motors
- Maximum material: 1000 x 500 x 18mm (LxWxT)
- Maximum hole: Ø30x20mm
- Sturdy frame construction and servo motors driven.
- Hydraulic clamps for strong grip of material
- Hydraulic stripper with exchangeable plates
- Ball transfer units on the support table
- Safety covers with interlock switch
- Sensor for the air-oil booster to ensure clamping pressure
- Adjustable servo motor speed for various material sizes

Pre-Commissioning:

1. Punching machine is run & tested prior delivery
2. Hydraulic oil is included with machine

Includes

- Fully-automatic CNC table 1000 x 500mm (X & Y-Axis)


Optional Accessories

PC Based Control Upgrade

Product Brochure For P196F

- Multi Tool Punch System 30-30-30
- Multi Tool Punch System 30-40-30
- Auto Lubrication System
- Oil Tank Cooling System

Specific Features



CNC Punch Table

Recommended Accessories

P163

Laser Guide System

P165

Ø6-26mm Round Punch & Dies Set

P166

Ø11-40mm Round Punch & Dies Set


M800

Rubber Mat - Anti-Fatigue



Product Brochure For P196F

M805
 Rubber Mat - Anti-Fatigue



O000
 SpillFix Universal Organic Absorbent



O043
 Rust & Corrosion Preventive



O042
 General Purpose Lubricant & Corrosion Inhibitor



O040
 Rust & Corrosion Preventive



O044
 Rust & Corrosion Preventive



O004
 Superdraulic ISO 46 Hi Temp Hydraulic Oil

