

Product Brochure For S631

Bead Roller - Motorised Variable Speed - MBR-475XT

1.2mm Mild Steel Thickness Capacity & 475mm Throat Depth

Includes 7 Sets of Hardened Rolls

On Sale

Ex GST

Inc GST

~~\$890.00~~

~~\$979.00~~

\$817.27

\$899.00



ORDER CODE:	S631
MODEL:	MBR-475XT
Machine (Type):	Bead Roller - Motrised
Mild Steel - Thickness Capacity (mm / Gauge):	1.2 / 18
Aluminium - Thickness Capacity (mm / Gauge):	1.6 / 16
Throat Depth Maximum (mm):	475
Throat Height (mm):	50
Roll Diameter (mm):	52
Output Drive Speed (rpm):	~
Motor Power (kW / hp):	0.25 KW / 0.335
Voltage / Amperage (V / amp):	240 / 10
Nett Weight (kg):	70

METALMASTER



Description

The MBR-475XT motorised bead roller is much easier to use compared to manual machines to having your panels beaded in your home workshop or garage. Made from heavy plate steel and a 475mm throat depth making it perfect for strengthening any type of car roof, body panels, seals & guards etc.

The MBR-475XT also includes a stand that also stores the seven sets of the most common rolls required by any metal forming automotive enthusiasts or professional.

Features

- 1.2mm mild steel capacity
- Heavy steel plate dual wall construction for increased rigidity
- Inverter controlled variable speed
- Forward / reverse via foot pedals
- Ø25mm drive shafts
- 22mm spigot for mounting rollers

Includes


- 1/4" (6.35mm) bead roll set
- 3/8" (9mm) bead roll set
- 1/2" (12.7mm) bead roll set
- 1/16" (1.6mm) flange roll set
- 1/8" (3mm) flange roll set
- 1/4" (6.35mm) flange roll set
- Shearing roll set

Product Brochure For S631

Specific Features



Adjustable Top Shaft



475mm Throat Depth and 50mm Height



Adjustable Material Depth Stop



Dual Wall Frame



Speed Control On Off Safety Switch



Die Set Included



Die Rack Holder



2 x Rear Wheels For Mobility



Foot Control With Emergency Stop



Motor



Side View



Left Side View

Product Brochure For S631

Recommended Accessories

S6411

Forming Bead Roller Kit

S6412

Round Over Bead Roller Sets

