

Product Brochure For W2531B

# MIG/TIG/STICK WELDER - RAZOR 500 SWF

SKU: U11214

50-500 Amps Welding Current Range

**On Sale**

<b>Ex GST</b>	<b>Inc GST</b>
<del>\$5,908.18</del>	<del>\$6,499.00</del>
<b>\$5,700.00</b>	<b>\$6,270.00</b>



ORDER CODE:	W2531B
MODEL:	RAZOR 500 SWF
Type:	MIG / TIG / STICK & Multifunction Welder
Part Number:	U11214
Voltage (V):	415
Recommended Plug Amperage (amp):	32
Welding Current Range - MIG (amp):	30 - 500
Welding Current Range - STICK (amp):	10 - 500
Welding Current Range - TIG (amp):	20 - 500
Duty Cycle (% @ amp):	40 @ 500
Wire Spool Size (kg):	5 & 15
Ferrous Wire Size - Range (mm):	0.8 - 1.6
Stainless Steel Wire Size - Range (mm):	~
Aluminium Wire Size - Range (mm):	~
Recommended Generator (KVA):	40
Dimensions (mm):	1520 x 520 x 980
Nett Weight (kg):	91.2



## Description

Superior performance even in the harshest conditions, this powerful workshop machine delivers nothing less than top-tier weld quality. A separate wire feeder gives extra manoeuvrability. Push-Pull gun ready for heavy-duty welding. 4 geared wire drive system for the smoothest wire feeding experience.

### Smart-Set MIG

Getting set up for a weld has never been faster with our preset synergic programs. Simply select your wire type, wire size, gas type and material thickness, and the machine does the rest. It'll pick the optimal settings for your weld.

### Multi-Process

Get the job done quickly and efficiently with our versatile three-in-one welding machine. With the ability to perform MIG, TIG, and MMA welding all in one unit, it's also capable of running both gas-shielded and gasless MIG wire, so you can tackle a wide variety of welding projects with ease. Whether you're working with mild steel, stainless steel, aluminium, or flux-cored wire, our machine has got you covered, saving you valuable time and effort without sacrificing quality.

### HD Backlit Interface

This next-generation interface panel is bright and easy to read in any environment.

### 4 Geared Wire Drive

The most consistent and smoothest wire-feeding experience there is. With a four geared wire drive unit, there's more power pushing the wire, improving the wire feeding, especially in longer torches.

### Digital Control MIG Torch

Our digital MIG torch allows you to adjust your settings on the fly. No more hassle of constantly adjusting your settings on a separate control panel. With our leading technology, you can easily fine-tune the amps, current and voltage at the touch of a torch button.

### Accessories

Ready for any kind of welding you've got planned, connect a complete range of MIG, TIG or MMA accessories to your welder.

**Spool Gun:** Make welding aluminium even easier. No need to change your existing setup. The spool gun lets you quickly switch over and get any job done with no downtime.

**Push-Pull Gun:** Achieve smooth and steady wire feeding, especially when using softer wires such as aluminium. With a 'Pull' motor built into the torch, the wire can be fed over a greater distance, granting you the freedom to move and manoeuvre with ease while MIG welding.

**Tig Torch:** The Trigger Controlled DC Lift Arc ignition allows the arc to be started easily in DC TIG by simply touching the tungsten to the workpiece and lifting it up to start the arc. This stops the tungsten tip sticking to the workpiece and breaking the tip from the tungsten electrode.

## Product Brochure For W2531B

### Inverter Technology

Not every inverter is made equal. With UNIMIG's ever-evolving, state-of-the-art IGBT Inverter technology, you get better performance, better efficiency, and better reliability.

### Smart Fan

Smart Fan diminishes noise, saves power, helps reduce energy costs, and minimises the number of contaminants being pulled through the machine.

### IP23S

Rated IP23S, so it's protected from touch by fingers and objects greater than 12mm, and water spray less than 60° from vertical while still.

### Advanced MMA Features

Advanced MMA features are designed for improving weld quality and ease of use.

**Arc Force:** The Arc Force feature helps to keep the arc stabilised throughout the weld, by increasing or decreasing the peak current to compensate for your arc length, preventing the arc from cutting out or the electrode from sticking.

**Anti-Stick:** The Anti Stick feature, which is always on, prevents your electrode from sticking to your workpiece. When the machine detects sticking, the current will drop significantly, so the electrode can be removed.

### Additional Features

**Separate Wire Feeder:** Get the ultimate flexibility. The addition of a separate wire feeder means you can detach the wire feeder from the main power source, giving you an extra 10m of manoeuvrability.

**Job Memory:** The job memory function allows you to enter and store weld parameter settings. Weld parameters can be further adjusted and stored as required. A total of 10 jobs can be memorised and stored for recall.

**Large Wire Spool Capacity:** Fits both D200 and D300 wire spools, so you can put 15kg mild steel or 7kg aluminium spools in the machine.  
**Generator Compatible:** Take it anywhere. Connect the machine to a generator and use it wherever, whenever you need it. We recommend 40kVA for this machine.

### Includes

- RAZOR SWF 500 Welder
- 3m M350 Digital MIG Torch
- 4m Twist Lock Electrode Holder
- 4m 500A Earth Clamp & Lead
- Twin Gauge Argon Regulator
- 1.8m Quick-Connect Gas Hose
- Operating Manual
- 2 x 0.8-0.9mm V Groove Rollers
- 2 x 1.0-1.2mm V Groove Rollers
- 2 x 0.8-0.9mm F Groove Rollers
- 2 x 1.0-1.2mm F Groove Rollers
- 4 x 1.0-1.2mm U Groove Rollers

### Specific Features



Front View



Left View



HD Backlit Interface



4 Geared Wire Drive

Product Brochure For W2531B

**Recommended Accessories**

**W501A**

M350 MIG Torch Consumables Starter Kit



**W5013A**

M350/M580W 1.0mm Contact Tips - Aluminium



**W5014A**

M350/M580W 1.2mm Contact Tips - Aluminium



**W5011**

M350/M580W 0.8mm Contact Tips - Steel



**W5012**

M350/M580W 0.9mm Contact Tips - Steel



**W5013**

M350/M580W 1.0mm Contact Tips - Steel



**W5014**

M350/M580W 1.2mm Contact Tips - Steel



**W5015**

M350 Conical Insulated Gas Nozzles



Product Brochure For W2531B

**W5017**  
 M350 Tip Adapter



**W10362**  
 Magnetic MIG Torch Rest



**W10361**  
 Magnetic TIG Torch Rest



**W119**  
 Anti-Spatter Spray



**O0184**  
 Ar/O2 - Argon 98% & Oxygen 2% Disposable Cylinder



**O0185**  
 CO2/Ar - 86% Argon & 14% Carbon Dioxide Disposable Cylinder



**O300**  
 Gas Refillable Cylinder



**O304**  
 Gas Refillable Cylinder



**O3045**  
 Gas Refillable Cylinder



**O302**  
 Gas Refillable Cylinder



**O306**  
 Gas Refillable Cylinder



**O3065**  
 Gas Refillable Cylinder



Product Brochure For W2531B

O0171  
 Argon Gas Regulator



W160A  
 Argon Gas Regulator-Twin Gauge



W161  
 Argon Gas Regulator-Bobbin Flowmeter



W001  
 Auto Darken Welding Helmet - 9-13 Shade



W002  
 Auto Darken Welding Helmet - 9-13 Shade



W1000A  
 Promax HV5 Welding Jacket



W1001A  
 Promax Blue FR Welding Jacket



W1002A  
 Professional Promax BL7 Welding Jacket




W100  
 ROGUE™ Heavy Duty Welding Gloves - 400mm



W101  
 TIG Welding Gloves - 310mm



L3456  
 How to Weld Book



W225  
 Welding Curtain



Product Brochure For W2531B

**W135**  
 Ø0.9mm Mild Steel MIG  
 Welding Wire



**W136**  
 Ø0.8mm Mild Steel MIG  
 Welding Wire



**W138**  
 Ø0.6mm Mild Steel MIG  
 Welding Wire



**W138A**  
 Ø0.6mm Mild Steel MIG  
 Welding Wire



**W140**  
 Ø0.8mm Mild Steel MIG  
 Welding Wire



**W140A**  
 Ø0.8mm Mild Steel MIG  
 Welding Wire



**W142**  
 Ø0.9mm Mild Steel MIG  
 Welding Wire



**W143**  
 Ø1.0mm Aluminium MIG  
 Welding Wire



**W144**  
 Ø1.2mm Aluminium MIG  
 Welding Wire



**W145**  
 Ø0.9mm Gasless Mild Steel  
 MIG Welding Wire



**W145A**  
 Ø0.9mm Gasless Mild Steel  
 MIG Welding Wire



**W125**  
 Ø1.6mm TIG Filler Rod - Mild  
 Steel



Product Brochure For W2531B

W126

Ø2.4mm TIG Filler Rod - Mild Steel



W127

Ø1.6mm TIG Filler Rod - Stainless Steel



W128

Ø2.4mm TIG Filler Rod - Stainless Steel



V099

90 degree Angle Vice Clamp



V100

90 degree Angle Vice Clamp

