

Product Brochure For W415A

## Thicknesser - HSS Blades - T-20A

508 x 200mm (W x H) Material Capacity  
 Includes 4 x High Speed Steel Blades

**On Sale**

<b>Ex GST</b>	<b>Inc GST</b>
<del>\$3,850.00</del>	<del>\$4,235.00</del>
<b>\$3,540.00</b>	<b>\$3,894.00</b>



ORDER CODE:	W415A
MODEL:	T-20A
Material Width Capacity (mm):	508
Material Height Capacity (mm):	200
Minimum Material Length (mm):	190
Maximum Depth of Cut (mm):	6mm @ 508mm wide
Cutter Type:	HSS Blades - Straight
Quantity of Cutters (No. x Type):	4 x Blades
Cutter Block Diameter (mm):	80
Cutter Block Speed (rpm):	5000
Quantity of Spirals (No.):	~
Length of Table (mm):	650
Length of Table with Extensions/Rollers (mm):	1470
Feed Speed (m/min):	4.8 / 6
Dust Outlet Diameter (mm):	125
Motor Power (kW / hp):	2.25 / 3
Voltage / Amperage (V / amp):	240 / 20
Floor Space (W x D x H) (mm):	1000 x 1470 x 1030
Floor Space With Option Stand (W x D x H) (mm):	~
Nett Weight (kg):	420



### Description

The Hafco T-20A thicknesser manufactured in Taiwan with four knife cutter head is a heavy duty machine with very substantial cast iron body and heavy gauge sheet steel base. The cast iron thickening table which has a polished surface to help timber slide freely as well as to help reduced vibration to improved quality of cut.

The cutter head is supported by 4 x solid pillars at each corner and the steel drive rollers have ribbing to ensure positive grip on the timber through the machine via two speed gearbox at a rate of 16 or 20rpm. The feed roller pressure can be adjusted with the four adjusters on the top of the machine. The depth of cut is set by means of the cranked handle on the side using the setting scale positioned on the in-feed side or digital readout.

Power is provided by a 2250 / 3hp 240V induction motor, housed within the base and transmitting power to the cutter block via a twin pulley vee belt drive system.

### Features

- Suits professional workshop
- Heavy cast iron machine
- 4 x HSS blades pre-set in cutter head with quick action blade change
- Cutting speed 5000 rpm
- 2 speed feed rollers with pressure adjustment
- 125mm dust chute
- Digital Height Gauge (Includes LR44 battery)
- Industrial contactor switch with overload protection
- Anti kick back fingers
- Left & right table locking dials
- Heavy duty four post design with protective concertina covers
- Same model sold for over 20 years
- Quality Taiwanese Manufacture

- Please Note:
- This machine is not supplied with a 240 volt plug

Product Brochure For W415A

Specific Features



2 Speed Feed Gearbox



Digital Height Readout



Magnetic Safety Switch



Robust 4 Post Design

Recommended Accessories

WL005  
 BLADE SET HSS PKT 4



W754  
 Spiral Cutter Head - Carbide Inserts



W394  
 Dust Collector



W931  
 Mobile Base - Heavy Duty



W329  
 Dust Collector



W344  
 Wood Dust Accessory Kit



W334  
 Dust Hose Reducer



W333  
 Dust Hose Reducer



Product Brochure For W415A

**W335**  
 Blast Gate



**W336**  
 Dust Hose Elbow - 90 Degree



**W337**  
 Dust Hose Y Adaptor



**W338**  
 Dust Hose Universal Dust Hood



**W339**  
 Dust Hose Floor Sweeper Attachment



**W340**  
 Dust Hose Clamp



**W341**  
 Dust Hose Clamp



**W343**  
 Roller Stand



**W343A**  
 Roller Stand



**W3434**  
 Roller Stand

