

Product Brochure For W4230

Wood Band Saw - BP-355H

Blade Speed 800m/min
 345mm Throat Depth x 300mm Height Capacity



On Sale - New Release

Ex GST	Inc GST
\$1,690.00	\$1,859.00
\$1,590.00	\$1,749.00

ORDER CODE:	W4230
MODEL:	BP-355H
Wheel Diameter (Ø) (mm):	355
Throat Capacity (mm):	345
Height Capacity (mm):	300
Table Size (mm):	540 x 480
Frame Type:	Steel
Motor Power (kW / hp):	1.7 / 2.5
Voltage / Amperage (V / amp):	240 / 10
Blade Code (Suits):	W4230A, W4230B, W4230F
Blade Size (L x W x T) (mm):	2920 x 6-19 x 0.9
Floor Space (W x D x H) (mm):	680 x 600
Nett Weight (kg):	132



Description

The BP-355H woodworking bandsaw is designed for serious performance, accuracy, and safety in both professional and advanced workshop environments. Featuring an impressive 300mm cutting height capacity, it handles deep resawing and large stock with ease. The rigid, steel-fabricated frame ensures exceptional stability and vibration reduction, delivering smooth, accurate cuts every time.

Precision is enhanced through ball bearing blade guides and a rack-and-pinion adjustable top blade guide, allowing fast, accurate setup and consistent blade tracking. The cast iron table provides a solid work surface and tilts up to 45° for angled cuts, while the high/low rip fence offers flexibility for a wide range of cutting tasks.

A quick-release blade tension mechanism and a blade tension indicator with viewing window make blade changes fast and reliable. Integrated blade guards with safety interlocked micro-switches, along with a magnetic safety switch and emergency stop, provide comprehensive operator protection. Powered by a robust 1.7kW (2.5hp) 240V induction motor and equipped with a 100mm dust extraction port, this bandsaw delivers powerful, clean, and dependable performance for demanding woodworking applications.

Features

- Large cutting height capacity of 300mm
- Ball bearing blade guides
- High / Low rip fence
- Heavy duty steel fabricated frame
- Cast iron table tilts to 45°
- Rack & pinion adjustment on top blade guide
- Quick-release blade tension mechanism
- Blade tension indicator with viewing window
- Blade guards with safety interlocked micro-switches
- Safety magnetic switch with emergency stop
- 100mm dust collector port
- 1.7kW / 2.5hp 240V induction motor

Includes

- Mitre guide
- Quick lock rip fence
- Enclosed stand

Product Brochure For W4230

Specific Features



Shown with Table at 45 Degrees



Right Side View



Rear View



Left View




Blade Guide Scale



Blade Guide Hand Wheel



Ball Bearing Blade Guides



Adjustable Ball Bearing Blade Guides



Mitre Guide



Sliding Rip Fence Up Position



Sliding Rip Fence Down Position



Sliding Rip Fence Scale



Switches



Large Cast Iron Table



Table Tilts to 45 Degrees



Safety Micro Switch on Doors

Product Brochure For W4230



Blade Cleaning Brush



Blade Speed 800 metres per minute



Shown With Blade Guards Open



Heavy Duty Cast Iron Wheels



Blade Tension Window




Blade Viewing Window



Quick Action Blade Tension Lever



100mm Side Dust Chute



Material Push Stick

Product Brochure For W4230

Recommended Accessories

W4230A

Wood Band Saw Blade - 6TPI,
 Blade - 2920 x 13 x 0.9mm



W4230B

Wood Band Saw Blade - 3TPI,
 Blade - 2920 x 12 x 0.9mm



W4230F

Wood Band Saw Blade - 6TPI
 Narrow, Blade - 2920 x 6 x
 0.65mm



W309

Safety Push Blocks & Stick Set



W311

Ripping Gauge



W3130

Twin Feather Board Set



W930

Mobile Base



W931

Mobile Base - Heavy Duty



Product Brochure For W4230

W332
 Dust Collector



W886
 Dust Collector



W344
 Wood Dust Accessory Kit



W334
 Dust Hose Reducer



W333
 Dust Hose Reducer



W335
 Blast Gate



W336
 Dust Hose Elbow - 90 Degree



W337
 Dust Hose Y Adaptor



W338
 Dust Hose Universal Dust Hood



W339
 Dust Hose Floor Sweeper Attachment



W340
 Dust Hose Clamp



W343
 Roller Stand

