

Product Brochure For W572

## MIG Torch - 3 Metre - SB36-3M

3 Metre  
 Suits 335-400 Amp



**On Sale - Special Order**

Ex GST	Inc GST
<del>\$200.00</del>	<del>\$220.00</del>
<b>\$169.09</b>	<b>\$186.00</b>

ORDER CODE:	W572
Part Number:	SB36-3M
Type:	MIG Torch
Amperage (amp):	300
Electrical Pin Connector:	~
Duty Cycle Rating: CO2:	60% @ 300amp
Duty Cycle Rating: Mixed Gas:	60% @ 270amp
Includes U-Groove Roller (mm):	~
Wire Size Capability (mm):	0.6 - 1.2
Torch Connector (Type):	Euro Connector



### Description

Suregrip Series  
 SB36 MIG Torch

### Features

- 300A AIR COOLED MIG WELDING TORCH
- Rating:300A CO<sup>2</sup>
- 270A mixed gas
- EN60974-7 @ 60% duty cycle
- 0.8 to 1.2mm wires

Product Brochure For W572



**Unimig**  
 Suregrip Series

**Consumable parts**

All wear and spare parts are manufactured to the same specification as the OEM and are fully interchangeable.

**Hanger Hook**

A "plug and play" option, they encourage the operator to hang the torch off the ground where it is easy to locate.

**Medium Ergo Trigger Assembly**

Rapid field servicing ensured by a simple "plug and play" system. Switches can be exchanged in 5 seconds without the use of tools.

**Knuckle Joint and Cable Support**

Small movements of the handle and neck are possible independent of the cable assembly. A moulded polymer cable support increases flexibility and electrode support.



**Spring Pins**

Fitted with unbreakable spring loaded gun plug body pins.

**Rear Cable Support**

Extra length cable support systems ensure smooth and consistent wire feed at any angle.

**Swan Necks**

Manufactured to the same specification as the OEM.



**Ergo Handle**

A patented screwless design combines the ultimate in balance, positioning and ergonomics. Torch handles disassemble in 5 seconds for rapid fault analysis. Top and bottom handle soft grips ensure all day welder comfort.

**Hyperflex Cable Systems**

Air cooled cable assemblies offer outstanding flexibility with the highest heat and abrasion resistance of any known cable. The outer jacket is constructed from cross-linked polymers providing a tear proof outer with a burn threshold of 375°C.



**Gun Plug Housing**

Tough and damage resistant, housings and nuts are formed in robust glass-reinforced polymers encasing all conductive parts in accordance with EN60974-7.

Product Brochure For W572

**Recommended Accessories**

**W10362**  
 Magnetic MIG Torch Rest

**W539**  
 0.6-0.8mm Blue Steel Liner

**W538**  
 1.0-1.2mm Red Steel Liner

**W567**  
 1.0-1.2mm Red Aluminium Liner



**W564**  
 2 x Conical Nozzles

**W576**  
 2 x Gas Diffusers

**W568**  
 Swan Neck Assembly

