

Product Brochure For W629

Planer Jointer - P-200H

200mm Width Capacity
 13mm Rebate Capacity



On Sale - Back In Stock Soon

Ex GST	Inc GST
\$1,350.00	\$1,485.00
\$1,250.00	\$1,375.00

ORDER CODE:	W629
MODEL:	PT-200H
Width Capacity (mm / inch):	200 / 8
Maximum Depth of Cut (mm):	3
Table Length (mm):	1800
Length of Infeed Table (mm):	870
Length of Outfeed Table (mm):	875
Rebate (mm):	13
Fence Length x Height (mm):	885 x 125
Blade Cutter (Type):	HSS
Blade Quantity (No.):	4
Cutter Block Diameter (mm):	~
Cutter Block Speed (rpm):	5500
Dust Port Diameter (mm):	100
Motor Power (kW / hp):	1.5 / 2
Voltage / Amperage (V / amp):	240 / 10
Floor Space (W x D x H) (mm):	1800 x 700 x 1120
Nett Weight (kg):	208



Description

The PT-200H Industrial Planer Jointer is extremely rugged in construction & weighing in at 208kg it will not move when planing heavy timber. With 2 x independently adjustable cast iron tables, 4 x HSS cutter blades rotating at 5500rpm and a powerful 2hp 240V motor driving the 200mm wide cutter head making it a very popular choice for trade professional joinery workshops.

This cast iron infeed and outfeed tables are a long 1800mm in total length, and ground exceptionally flat and mounted on a substantial steel stand. The power switch is conveniently mounted up high to the side of the table for quick & easy access. For safety, the cutter blades are fully protected across its whole width by a spring return aluminium guard that self regulates to your timber size. The infeed and outfeed tables can also be adjusted for a quick set up to produce rebates up to 13mm deep. There also is an adjustable quick stop system on the infeed table to allow repeat accurate depth settings to be made quickly.

The heavy duty cast iron adjustable fence with a flat ground surface, is held by a robust cast iron bracket & slide system. The fence is fully adjustable for angles between 45°, 90° & 135°. Waste extraction is removed from the left side of the machine via a 100mm outlet port and should be connected to a suitable dust extractor.

Setting the four HSS blades into the cutting block is easy & accurate with the included blade setting gauge device, ensuring that all blades are accurately set in identical position for a smooth cut finish.

Features

- Heavy duty machine
- 200mm width capacity
- 4 x HSS blade cutter head
- Extra longer 1800mm cast iron table
- 13mm rebating capacity
- Adjustable in & out feed tables
- Rigid quick action tilting fence to 45° L & R with adjustable stops
- Magnetic safety switch with paddle emergency stop
- Spring loaded blade guard
- Feed handle with locking bar
- Enclosed stand with 100mm dust chute
- 1.5kW / 2hp 240V motor

Product Brochure For W629

Specific Features



Left View



Rear View



Side View



Adjustable Quick Action Tilt Fence Assembly



On-Off Switch



Dust Chute & Out-feed Table Height Adjustment Handle



Blade Cutting Head



Cutter Safety Guard



Included Accessories

Product Brochure For W629

Recommended Accessories

2TC0202
 BLADES 4PC



W309
 Safety Push Blocks & Stick Set



W763
 Spiral Cutter Head with Carbide Inserts



W332
 Dust Collector



W394
 Dust Collector



W344
 Wood Dust Accessory Kit



W334
 Dust Hose Reducer



W333
 Dust Hose Reducer



Product Brochure For W629

W335
 Blast Gate



W336
 Dust Hose Elbow - 90 Degree



W337
 Dust Hose Y Adaptor



W338
 Dust Hose Universal Dust Hood



W339
 Dust Hose Floor Sweeper Attachment



W340
 Dust Hose Clamp



W930
 Mobile Base



W343
 Roller Stand



W343A
 Roller Stand



W3434
 Roller Stand



W952
 Wood Band Saw

